

Area Monitors

GRAETZ WS05C-1 / C-2 / C-3

The area monitors WS05C-1 / WS05C-2 and WS05C-3 are stationary room monitoring systems for the dose rate measurement of \dot{U} -radiation and X-rays, preferably used for the permanent monitoring of isotope laboratories, radiotherapy rooms, storage rooms for radioactive materials, etc..

The WS05C is available in the following versions:

- WS05C-1: Area monitor (1 measuring channel) with RS232-interface for the operation with any probe of the GRAETZ-programme.
- WS05C-2: Area monitor (2 measuring channels) with RS232-interface for one measuring channel, for the simultaneous operation of max. 2 different or similar probes - any of the GRAETZ-programme.
- WS05C-3: Area monitor (3 measuring channels) with RS232-interface for one measuring channel, for the simultaneous operation of max. 3 different or similar probes - any of the GRAETZ-programme.

Each measuring channel indicates the measured values on a digital, illuminated LC-display (60x30 mm). For each measuring channel four individual dose rate alarm thresholds are free programmable over the whole measuring range of the connected probes.

When using \dot{U} -probes, the dose rate shown on the LC-Display is Sv/h. When an end-window probe for β -/ \dot{U} -measurements or a NaI-scintillation probe for \dot{U} -measurements is connected, the measured value is displayed in cps. Additionally to the digital display, the dose rate is also indicated in analog form by a logarithmic bar graph.

The instrument is autoranging. When a measuring channel triggers a dose rate alarm, the integrated alarm light of the WS05C gives an optical and acoustical alarm. In the standard version: green $\hat{=}$ "ready for operation", orange $\hat{=}$ "alarm threshold exceeded" / red $\hat{=}$ "error" (e.g. defective probe). The red LED situated above the display indicates by which measuring channel the alarm has been triggered.

For connecting the WS05C with a computer, an RS232-interface for one measuring channel is available.

Options

- Relay output for an additional external alarm lamp for each measuring channel or a potential free relay output for each measuring channel instead of the relay output for the external alarm lamps (max. switching voltage/current: 24V, 20 mA).
- Acoustic alarm disconnectible: only triggered when an alarm threshold is exceeded and the monitored room's door is open.
- Emergency power supply (300W) for the uninterruptible operation of the WS05C in case of mains failure.
- External alarm lamps (optical/acoustical)
- Probe cable (standard length: 1,25 m), extension up to 100 m
- Special versions upon request





Technical Data WS05C

- Types: WS05C-1 for the connection of one probe (1 channel)
WS05C-2 for the simultaneous connection of max. 2 probes (2 channels)
WS05C-3 for the simultaneous connection of max. 3 probes (3 channels)
- Probes: The probes are preferably connected by means of a probe cable (up to 100 m) or directly to the sockets of the WS05C.
- Measurand: ambient dose rate equivalent rate $\dot{H}^*(10)$ for CE-probes

Available probes
The PTB-approval of the probes is only valid when used together with the dose rate meter X5C *plus*.

Probe type	Measuring range	PTB-approved measuring range ¹⁾
18545 CE	0 nSv/h - 200 μ Sv/h	150 nSv/h - 200 μ Sv/h (\dot{U} -radiation and X-rays)
18550 CE	0 nSv/h - 20 mSv/h	10 μ Sv/h - 20 mSv/h (\dot{U} -radiation and X-rays)
18529 CE	0 μ Sv/h - 10 Sv/h	0,5 mSv/h - 10 Sv/h (\dot{U} -radiation and X-rays)
18509 CE	0 μ Sv/h - 1 Sv/h	50 μ Sv/h - 1 Sv/h (\dot{U} -radiation and X-rays)
18526 D	cps, α -, β -, γ -radiation	
Nal-Scintillation probe 2002	cps, β -/ γ -radiation	

¹⁾ PTB-approved measuring range for measurements specifically demanded by German authorities

Measuring accuracy: " \pm 10%

Display: each measuring channel is equipped with an illuminated LC-display

Indication: - digital indication in Sv/h or cps, depending on the connected probe
- analog indication by a logarithmic bar graph

Alarm: - probe failure alarm
- dose rate alarm thresholds 1 - 4
- dose alarm thresholds 1 - 4

Alarm signals: - integrated optical/acoustical signal, triggered when a connected probe signalizes a dose rate alarm (orange) and/or an error (red)
- red LED for alarm indication when an alarm thresholds is triggered (at each measuring channel)

Interface: RS232 for one measuring channel (WS05C-2 / WS05C-3 \uparrow first measuring channel)

Dose rate alarm thresholds: for each measuring channel 4 dose rate alarm thresholds free programmable over the whole measuring range of the connected probe(s)

Dose alarm thresholds: for each measuring channel 4 dose alarm thresholds free programmable over the whole measuring range of the connected probe(s)

Temperature range: 0 °C up to +40 °C for the area monitor
-30 °C up to +60 °C for the probes

Humidity: max. 90% relative humidity

Power supply: 90-260V AC 200 mA max. 50/60 Hz

Housing: plastic, high-impact

Dimensions: 260 mm x 230 (455) mm x 150 mm

Weight: approx. 2,8 kgs



GRAETZ Strahlungsmess-technik GmbH
Westiger StraÙe 172 · 58762 Altena / Germany

Distribuito in Italia da:

 **Active Radsys**

www.activeradsys.it www.activeradsys.it