

RTM 1688-2



Technical Data

- Optimised high voltage chamber with electrostatic focus of short living Radon daughters generated inside the chamber at the surface of a semiconductor detector
 - No changes of the sensitivity due to the ambient humidity
 - **Usage of a drying tube or similar equipment is NOT required!**
 - High sensitivity at low chamber volume (approx. 250 mL)
- Spectrometric analysis of the short living Radon daughters
 - Minimum possible response time using the Fast-Mode (90% of the final value within 10 Minutes)
 - Double sensitivity using the Slow-Mode (including Po-214)
 - Measurement of the Thoron (Rn-220) concentration
 - No contamination by long living Radon daughters
 - 100% quality assurance by readable Alpha spectrums
- Measurement Range 0 ... 10 MBq/m³
- Sensitivity 3/7 counts/Minute @ 1000 Bq/m³ (Fast/Slow-Mode)
 - 200 Bq/m³ with a 10% statistical error (1 σ) at a 1h sample interval
 - 10 Bq/m³ with a 25% statistical error (1 σ) at a 4h sample interval
- Sensors included for
 - Relative humidity (0 ... 100%)
 - Temperature (-20 ... 40°C)
 - Barometric pressure (800 ... 1200mbar)
 - Tamper
- Sample interval from 1 Minute to 4 hours, 1 Minute steps
- Non-volatile memory for 2047 data records (circular), Alpha Spectrum for each included
- Internal sampling pump (0.30 L/min continuous and interval mode)
- Power supply by AC/DC wall adapter and internal rechargeable battery (battery operation up to 14 days)
- One button control (lock-function)
- Display (3 x 16 characters) with back-light
- RS232 and USB interface for set-up and data transfer (also via modem or ZigBee)
- Internal buzzer for alert function and Radon-„Sniffing“
- Dimensions 232 x 182 x 135 mm, weight 3.5 kg
- Radon Vision Software included

This specification sheet is for information purposes only and is subject to change without notice. SARAD GmbH makes no warranties, expressed or implied, in this product summary. © SARAD GmbH. All rights reserved.



Distribuito in Italia da:



www.activeRadsys.it info@activeradsys.it
Tel- 0544 408071 Fax: 0544 276014