

DOSE_{man} PRO



Technical Data

Theory of Operation	Collection of the Radon daughter products at the surface of a filter by a continuous air flow permanent alpha spectroscopic analysis of the filter
Filter	0.8 µm Membrane filter (PTFE) Diameter 17.5 mm 1 month replacement interval under normal conditions
Pump	Membrane pump 0.18 Lpm
Sensitivity	approx. 150 cpm @ 1000 Bq/m ³ (EEC)
Response time	2 hours (to 90% of the final value)
Integration interval	1 ... 255 Minutes, adjustable in 1 Minute steps
Operation	Single push button with „Lock“ function Display 3 x 12 characters, either US or SI units Acoustic alert
Memory	377 records and sum spectrum, non-volatile
Interface	Infrared data link with special adapter for the USB-Port of the PC
Power supply	internal rechargeable battery approx. 48 hours continuous operation Charging time approx. 2 hours
Housing	rough Aluminium enclosure with open sampling head Dimensions 138 x 57 x 32 mm Weight 300g
Software	Radon Vision

This specification sheet is for information purposes only and is subject to change without notice. SARAD GmbH makes no warranties, expressed or implied, in this product summary. © SARAD GmbH. All rights reserved.



SARAD GmbH, Wiesbadener Str. 10, 01159 Dresden, Germany

Distribuito in Italia da:



www.activeRadsys.it info@activeradsys.it

Tel- 0544 408071